



RT700i / RT730i

Powerful Barcode Printer for most demanding jobs

Full functions, powerful features, user friendly interface and high extensibility make the RT700i perfect for retail and industrial applications.



Color TFT LCD and operation panel for easy and intuitive operation



Ethernet, USB 2.0, Serial and USB host are standard features adding flexibility and power



Rod-less label roll holder for easy loading and smooth feeding



Innovative "C" button makes label Calibration simple and fast

Barcodes Made Easy

Product Specifications
RT700i / RT730i Desktop Printer

Model	RT700i	RT730i
Print Method	Thermal Transfer/Direct Thermal	
Resolution	203 dpi (8 dots/mm)	300 dpi (12 dots/mm)
Print Speed	Up to 7 IPS (177 mm/s)	5 IPS (127 mm/s)
Print Width	4.25" (108 mm)	4.16" (105.7 mm)
Print Length	Min. 0.16" (4 mm)**; Max. 68" (1727 mm)	Min. 0.16" (4 mm)**; Max. 30" (762 mm)
Memory	8 MB Flash (4 MB for user storage)	
Flash	16 MB SDRAM	
Sensor Type	Adjustable reflective sensor (full range) Fixed transmissive sensor, central aligned	
Types	Continuous form, gap labels, black mark sensing and punched hole; label length set by auto sensing or programming	
Width	1" (25.4 mm) Min. - 4.64" (118 mm) Max.	
Thickness	0.003" (0.06 mm) Min. - 0.01" (0.2 mm) Max.	
Label Roll Diameter	Max. 5" (127 mm)	
Core Diameter	1" (25.4 mm), 1.5" (38.1 mm)	
Types	Wax, wax/resin, resin	
Length	981' (300 m)	
Width	1.18" (30 mm) Min. - 4.33" (110 mm) Max.	
Ribbon Roll Diameter	2.67" (68 mm)	
Core Diameter	1" (25.4 mm)	
Printer Language	EZPL, GEPL, GZPL auto switch	
Label Design Software	GoLabel (for EZPL only)	
Driver	Windows 2000, XP, Vista, 7, Windows Server 2003 & 2008	
DLL	Windows 2000, XP and Vista	
Bitmap Fonts	6, 8, 10, 12, 14, 18, 24, 30, 16X26 and OCR A&B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical directions	
Scalable Fonts	90°, 180°, 270° rotatable	
Bitmap Fonts	Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable	
Asian Fonts	Asian fonts 90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions	
Scalable Fonts	Scalable fonts 90°, 180°, 270° rotatable	
1-D Bar codes	Code 39, Code 93, EAN 8 /13 (add on 2 & 5), UPC A/E (add on 2 & 5), I 2 of 5 & I 2 of 5 with Shipping Bearer Bars, Codabar, Code 128 (subset A, B, C), EAN 128, RPS 128, UCC 128, UCC/EAN-128 K-Mart, Random Weight, Post NET, ITF 14, China Postal Code, HIBC, MSI, Plessey, Telepen, FIM, GS1 DataBar	
2-D Bar codes	PDF417, Datamatrix code, MaxiCode, QR code, Micro PDF417, Micro QR code, Aztec code	
Code Pages	CODEPAGE 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737 Unicode (UTF8, UTF16)	
Graphics	Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software	
Interfaces	USB 2.0 Serial port: RS-232 (DB-9) Ethernet 10/100 Mbps print server USB Host	
Control Panel	Color TFT LCD with navigation button Power on/off button Calibration button	
Real Time Clock	Standard	
Power	Auto Switching 100-240VAC, 50-60Hz	
Operation Temperature	41°F to 104°F (5°C to 40°C)	
Storage Temperature	-4°F to 122°F (-20°C to 50°C)	
Operation	30-85%, non-condensing	
Storage	10-90%, non-condensing	
Agency Approvals	CE(EMC), FCC Class A, CB, CCC, cUL	
Length	11.0" (280 mm)	
Height	7.3" (186 mm)	
Width	8.3" (210 mm)	
Weight	6.6 lbs (3 Kg), excluding consumables	
Options	Bluetooth module Guillotine Cutter Label Dispenser External label roll holder for 10" (250 mm) O.D. label rolls External label rewinder	

* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.

** Minimum print height specification compliance can be dependent on non-standard material variables such as label type, thickness, spacing, liner construction, etc. Godex is pleased to test non-standard materials for minimum height printing capability.